

FVA-600 Variable Attenuator



SPEC SHEET

Delivers the highest performance within handheld optical attenuators on the market.

KEY FEATURES

- Most compact and rugged portable attenuator on the market
- Low cost of ownership: three-year warranty and recommended calibration interval
- Three operating modes: Absolute, Relative and Power
- Backlit display, optimized for dim environments
- USB-based remote control capability, for easy test routine integration
- Rechargeable Li-ion battery

APPLICATIONS

- Handles high power up to 24 dBm, suiting any application, including CATV and telco
- BER testing-ready: high optical resolution of 0.01 dB
- FTTx-ready: standard 1310, 1490, 1550 and 1625 nm wavelengths

COMPLEMENTARY PRODUCTS



SONET/SDH Test Modules
FTB-8115 – FTB-8120
FTB-8130 – FTB-8140




Optical Light Sources
FLS-300
FLS-600



Optical Power Meters
FPM-300
FPM-600





- 1 Backlit keyboard and screen
- 2 In/out universal optical interfaces
- 3 AC adapter
- 4 USB port for remote applications

SPECIFICATIONS^a

Fiber type (µm)	9/125
Calibration wavelengths (nm)	1310/1550
Wavelength range (nm)	1250 to 1625
Wavelength increment (nm)	1
Maximum attenuation (dB)	65
IL (dB) ^{b, c, d}	≤1.5
Resolution (dB)	0.01
Linearity (dB) ^{b, c, e}	±0.1
Repeatability 2σ (dB) ^c	±0.1
Optical return loss (dB) ^{f, h, i}	>50
Max. input power (dBm) ^g	24
Battery life (hours) ^e	>300
Warranty and recommended calibration interval (years)	3

GENERAL SPECIFICATIONS

Size (H x W x D)	190 mm x 100 mm x 62 mm (7 1/2 in x 4 in x 2 1/2 in)
Weight	0.6 kg (1.3 lb)
Temperature	operating: -10 °C to 50 °C (14 °F to 122 °F) storage: -40 °C to 70 °C (-40 °F to 158 °F)
Relative humidity	0 % to 95 % non-condensing
Power	AC adapter and rechargeable Li-ion battery

STANDARD ACCESSORIES

User guide, Certificate of Calibration, quick reference sticker in five languages, AC adapter/charger, connector adapter (EUI-XX), lithium ion battery, shoulder strap, semi-rigid carrying case, USB cable, instruction manual on CD

Notes

- a. At 23 °C ± 3 °C.
- b. At 1310 nm ± 30 nm.
- c. At 1550 nm ± 40 nm.
- d. Excluding connectors.
- e. Typical.
- f. At minimum IL.
- g. Prolonged exposure to maximum input power will impair linearity calibration.
- h. At 1310 nm ± 1 nm and 1550 nm ± 1 nm.
- i. Including connectors.

ORDERING INFORMATION

FVA-600-B-XX

Connector

EI-EUI-28 = UPC/DIN 47256	EA-EUI-28 = APC/DIN 47256
EI-EUI-76 = UPC/HMS-10/AG	EA-EUI-89 = APC/FC narrow key
EI-EUI-89 = UPC/FC narrow key	EA-EUI-91 = APC/SC
EI-EUI-90 = UPC/ST	EA-EUI-95 = APC/E-2000
EI-EUI-91 = UPC/SC	EA-EUI-98 = APC/LC
EI-EUI-95 = UPC/E-2000	
EI-EUI-98 = UPC/LC	

Example: FVA-600-B-EI-EUI-89

Az Ön mérés-technikai szakértője:



EXFO Headquarters > Tel.: +1 418 683-0211 | Toll-free: +1 800 663-3936 (USA and Canada) | Fax: +1 418 683-2170 | info@EXFO.com | www.EXFO.com

EXFO serves over 2000 customers in more than 100 countries. To find your local office contact details, please go to www.EXFO.com/contact.

EXFO is certified ISO 9001 and attests to the quality of these products. EXFO has made every effort to ensure that the information contained in this specification sheet is accurate. However, we accept no responsibility for any errors or omissions, and we reserve the right to modify design, characteristics and products at any time without obligation. Units of measurement in this document conform to SI standards and practices. In addition, all of EXFO's manufactured products are compliant with the European Union's WEEE directive. For more information, please visit www.EXFO.com/recycle. Contact EXFO for prices and availability or to obtain the phone number of your local EXFO distributor.

For the most recent version of this spec sheet, please go to the EXFO website at www.EXFO.com/specs.

In case of discrepancy, the Web version takes precedence over any printed literature.